




TW3X2G2133C9DF

The Dominator Series TW3X2G2133C9DF is a 2048MByte kit of DDR3 SDRAM DIMMs built using Corsair's latest high performance heat sink with Dual-path Heat Xchange (DHX) technology coupled with a Corsair Airflow Fan. This part delivers outstanding performance in the latest generation of dual-channel DDR3-based motherboards. It has been tested extensively in popular DDR3 motherboards to ensure compatibility and performance at its rated speed. This memory has been verified to operate at 2133MHz at latencies of 9-9-9-24 at 2.0V VDIMM.



Dual-path Heat Xchange Diagram

- Optimized fins to maximize ambient airflow through the module array
- Extruded aluminum heat sinks to maximize convective heat dissipation
- Dedicated PCB heat sink



TEST SPECS

- ▶ Each module pair is tested together at 2133MHz
 - ➔ Packaged together immediately following system test
- ▶ Tested together at 2133MHz, Vdimm = 2.0V, at latency settings of 9-9-9-24 on NVIDIA 790i-based motherboards with a dual core CPU
 - ➔ Must use sockets DIMM A2 and B2 ("black sockets") to achieve this performance
- ▶ SPD programmed at:
 - ➔ JEDEC standard 9-9-9-24 values at 1333MHz

FEATURES

- ▶ 2048 Megabytes of DDR3 memory
 - ➔ Two matched CM3X1G2133C9D modules
- ▶ DHX technology provides maximum cooling
- ▶ Includes Airflow Fan for maximum thermal transfer
- ▶ 100% tested at 2133MHz in NVIDIA-based motherboards
- ▶ Lifetime warranty

www.corsair.com

Every part is tested in Corsair's factory at 2133MHz, but your actual results may vary depending on the overclocking margin of your CPU and motherboard. Newer motherboards may be used for production test as they become available. Corsair may periodically update the part with newer RAM revisions of same or greater performance. RAM used on the module may change without notice. © June 2008 Corsair Memory, Inc.